



PARTNER
FOR THE EXPERTS

ah

Silent & Low Speed Granulator

SERIES

ah
SERIES

CREATE PRACTICAL VALUE WITH MECHANICAL AESTHETICS



Cutters of AH-Series granulator are for coarse crushing and fine crushing synchronized. Advance double-edges design of big jaw cutters for minimizing resistance during cutting, enhancing breaking up of sprue, coarse feed is subsequently palletized by toothed rollers, each roller tooth producing an equal sized pellet. (There are 4x4.5mm and 6x7 mm optional toothed rollers). This technology requires as low as a speed of (25-30 rpm) and Horse Power of (1-5 HP), reaching optimum possible low noise, low dust and uniform granules at a consistent rate. Ideal for using at night shift and low noise dust free operation condition.

ah

Silent & Low Speed Granulator

SERIES

AH系列粉碎機的刀具採粗碎與細碎同步進行，大型爪刀採最先進的雙刀刀設計，可降低阻力、增進切斷功能。粗碎後的顆粒經由滾齒狀刀具細碎成同等大小，尺寸分為4x4.5 mm與6x7 mm兩種，由於只需低轉速(25至30 rpm)、低馬力(1至5HP)，便可達到低噪音、粉末少、顆粒均勻等效果，特別適於夜間或低噪音無塵環境使用。

AH-150

AH-160

AH-260





Characteristics


- (1) The design of Pulian's claw blade is from traditional extrusion cut off. Even then improved the cutting quality. The blade edge improved is risen the cutting in excellent quality and reducing oscillate on the process of cutting.)
- (2) Low R.P.M to ensure that crusher machine in high quality and low-noise. High torque is to guaranty on the process of operation without barrier.
- (3) All machines have made of Pulian conforms to CE and CSA/UL Standard.

特點

- (1) 普聯的爪刀設計，從傳統的擠壓切斷改良為刀刀式切斷，不僅提升了切削品質，而且降低了切削過程中的振動力。
- (2) 低轉速確保粉碎料的最高品質與最低噪音，而高扭力是保證過程中平順無障礙。
- (3) 普聯各式機種均可製造符合CE、CSA/UL規範。



Composition	構圖			
MODEL	機型	AH-150	AH-160	AH-260
Tooth Cutter Size	齒刀尺寸	4x4.5 mm	4x4.5 mm	4x4.5 or 6x7 mm
Inlet Size	粉碎口徑	164x180 mm	164x260 mm	256x260 mm
R.P.M	轉數	30 rpm	30 rpm	30 rpm
Power	馬力	1/2 HP	2 HP	2HP
Machine Weight	機器重量	120 kg	170 kg	210 kg
Machine Size	機器尺寸	530x350x950 mm	650x760x940 mm	760x760x1000mm
Capacity	工作量	60~80 kg/hr	80~100 kg/hr	100~130 kg/hr

Composition	構圖				
MODEL	機型	AH-360A	AH-360B	AH-460	AH-560
Tooth Cutter Size	齒刀尺寸	4x4.5mm or 6x7mm	6x7 mm	6x7 mm	6x7 mm
Inlet Size	粉碎口徑	348x260 mm	350x320 mm	440x320 mm	680x440 mm
R.P.M	轉數	30 rpm	30 rpm	30 rpm	30 rpm
Power	馬力	3 HP	3 HP	5 HP	5 HPx2
Machine Weight	機器重量	250 kg	320 kg	415 kg	650 kg
Machine Size	機器尺寸	830x560x1300mm	760x920x1600mm	880x860x1180mm	1470x1000x1800mm
Capacity	工作量	110~150 kg/hr	130~180 kg/hr	150~200 kg/hr	150~250 kg/hr



AH-560刀具結構



AH-560

Characteristics

- (1) Inflation scrap/waste runner to be able to twin shaft design rapidly lay hands on to cutting chamber recycling.
- (2) The rotor is driven by independent machinery.
- (3) Automation reverses functional after overload.
- (4) Continuous reverse 3 times in a minute the machine will stop.

特點

- (1)寬鬆膨脹物能以雙爪，快速抓入刀室粉碎。
- (2)每個刀軸都具有獨立的傳動機構。
- (3)過載後自動反轉功能。
- (4)一分鐘內連續反轉3次自動停機功能。



AH-460刀具結構



傳動機構



CE開關CSA/UL

AH 標準型

AH CE CSA/UL型

AH-150 標準型

袋裝型

AH 系列的多種變化

自動排料型

加裝除粉型

改裝迷你型



最新產品相關資料，請連結至普聯公司網站查詢。

For updated information, please visit Pulian's website at URL <http://www.pulian.com.tw>